



Tubing Selection Comparison Table

To select the tubing that best fits your application, use the comparison table below. For more information on a specific tubing, visit us online at www.EJBeverage.com. For custom applications including special constructions, assemblies and thermoformed tubing, contact us at 970-667-2728.

Application	Tubing	Temp. Range °C	Temp. Range °F	Antimicrobial Protected	NSF 51	Shore A	Flexibility	Clarity	Barrier Properties	Price
Beer and Brewing	BFX Ultra Barrier™	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	73	★★★★★	★★★★★	★★★☆☆	\$
	BFX Ultra Barrier Silver™	-40 °C to 76 °C	-40 °F to 170 °F	✓		73	★★★★★	★★★★☆	★★★★★☆☆	\$\$
	BFX Ultra Barrier™ Gas (max 60 psi)	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	73	★★★★★	★★★★★	★★★☆☆	\$
	BFX High Temp™	-50 °C to 135 °C	-58 °F to 275 °F	-	✓	68	★★★★★	★★☆☆*	★★★☆☆	\$\$\$
	KFLEX	-50 °C to 80 °C	-58 °F to 176 °F	-	✓	85	★★★★☆	★★☆☆*	★★★★★☆☆	\$\$\$
Wine	BFX Ultra Barrier™	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	86	★★★★☆	★★★★☆	★★★★★☆☆	\$\$
	BFX Ultra Barrier Silver™	-40 °C to 76 °C	-40 °F to 170 °F	✓		86	★★★★☆	★★★★☆	★★★★★☆☆	\$\$\$
	BFX High Temp™	-50 °C to 135 °C	-58 °F to 275 °F	-	✓	68	★★★★★	★★☆☆*	★★★☆☆	\$\$\$
	KFLEX	-50 °C to 80 °C	-58 °F to 176 °F	-	✓	85	★★★★☆	★★☆☆*	★★★★★☆☆	\$\$\$
Dairy and Water	BFX Ultra Barrier™	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	73	★★★★★	★★★★★	★★★☆☆	\$
	BFX Ultra Barrier Silver™	-40 °C to 76 °C	-40 °F to 170 °F	✓		73	★★★★★	★★★★☆	★★★★★☆☆	\$\$
	BFX High Temp™	-50 °C to 135 °C	-58 °F to 275 °F	-	✓	68	★★★★★	★★☆☆*	★★★☆☆	\$\$\$
	Flexelene™ FX	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	86	★★★★☆	★★★★☆	★★★★★☆☆	\$
	Flexelene™ CFX (for push on fittings)	-40 °C to 76 °C	-40 °F to 170 °F	-		86	★★★★☆	★★★★☆	★★★★★☆☆	\$
	KFLEX	-50 °C to 80 °C	-58 °F to 176 °F	-	✓	85	★★★★☆	★★☆☆*	★★★★★☆☆	\$\$\$
General Beverage	BFX Ultra Barrier™	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	73	★★★★★	★★★★★	★★★☆☆	\$
	BFX Ultra Barrier Silver™	-40 °C to 76 °C	-40 °F to 170 °F	✓		73	★★★★★	★★★★☆	★★★★★☆☆	\$\$
	BFX High Temp™	-50 °C to 135 °C	-58 °F to 275 °F	-	✓	68	★★★★★	★★☆☆*	★★★☆☆	\$\$\$
	Flexelene™ FX	-40 °C to 76 °C	-40 °F to 170 °F	-	✓	86	★★★★☆	★★★★☆	★★★★★☆☆	\$
	Flexelene™ CFX (for push on fittings)	-40 °C to 76 °C	-40 °F to 170 °F	-		86	★★★★☆	★★★★☆	★★★★★☆☆	\$
	KFLEX	-50 °C to 80 °C	-58 °F to 176 °F	-	✓	85	★★★★☆	★★☆☆*	★★★★★☆☆	\$\$\$



For more information, visit us online at www.EJBeverage.com or contact us directly at 970-667-2728.

