



High Temp™

High Temperature
PVC-Free Tubing
Flexible
Medical and Food Grade

Superior Barrier Properties
Ultra-Low Permeability
Extremely Low Extractables

High Temperature

PVC-Free Food & Beverage High Temperature Tubing

High Temp™

PVC-Free Flexible High Temperature Tubing

EJ Beverage High Temp™ tubing is constructed of TPE (Thermoplastic Elastomer) which is an excellent alternative to high temperature PVC and Silicone. The advantages to this high temperature tubing are:

- PVC Free and Free of Silicone and BPA - contains no DEHP phthalates or other plasticizers
- Environmental friendly production - does not emit dioxins
- High temperature up to 135° C (275° F)
- Extremely low extractables / leachables
- Manufactured in an ISO Class 7 cleanroom environment
- Medical grade and NSF compliant material
- High flexibility
- Remains flexible at high temperatures
- Ultra-low permeability
- Barrier properties



Phone: 970-667-2728 • www.EJBeverage.com

High Temp™

PVC-Free High Temperature Tubing

High Temperature

Superior Barrier Properties

Standard Sizes

EJ Beverage High Temp™ is available in sizes from 3/16" I.D. up to 3/4" I.D. Thermoformed/coiled tubing, custom sizes and other special constructions are also available as special order.

Tube Number	Tube ID (A)		OD Nominal (B)		Wall Thickness	Standard Roll*
BFXHT 3-5	3/16"	.187"	5/16"	.312"	1/16"	100 ft.
BFXHT 3-7	3/16"	.187"	7/16"	.448"	1/8"	100 ft.
BFXHT 4-6	1/4"	.250"	3/8"	.385"	1/16"	100 ft.
BFXHT 4-8	1/4"	.250"	1/2"	.510"	1/8"	100 ft.
BFXHT 5-7	5/16"	.323"	7/16"	.448"	1/16"	100 ft.
BFXHT 5-9	5/16"	.323"	9/16"	.563"	1/8"	100 ft.
BFXHT 6-8	3/8"	.385"	1/2"	.510"	1/16"	100 ft.
BFXHT 6-10	3/8"	.385"	5/8"	.635"	1/8"	100 ft.
BFXHT 8-10	1/2"	.500"	5/8"	.635"	1/16"	100 ft.
BFXHT 8-12	1/2"	.500"	3/4"	.760"	1/8"	100 ft.
BFXHT 10-14	5/8"	.635"	7/8"	.885"	1/8"	100 ft.
BFXHT 12-16	3/4"	.760"	1"	1.010"	1/8"	100 ft.

Metric Sizes

Tube Number	Tube ID (A)		OD Nominal (B)		Wall Thickness	Standard Roll
BFXHT 4M-8M	4 mm	.157"	8 mm	.315"	2 mm	25 M
BFXHT 7M-12M	7 mm	.276"	12 mm	.472"	2.5 mm	25 M
BFXHT 10M-16M	10 mm	.394"	16 mm	.630"	3 mm	25 M

Temp. Range: -40°C to 135° C (-40°F to 275° F)

No DEHP or Phthalates

Low Extractables/Leachables

Superior Barrier Properties

High Flexibility

ISO 9001 and ISO 13485



Phone: 970-667-2728
www.EJBeverage.com

